




---

## DESCRIPTION AND RATING

---

**25AV5-GA Beam Pentode.** Identical to the 6AV5-GA except for heater ratings. Refer to the 6AV5-GA Description and Rating sheet for complete data.

**25AX4-GT Diode.** Identical to the 6AX4-GT except for heater ratings. Refer to the 6AX4-GT Description and Rating sheet for complete data.

**25BQ6-GA Beam Pentode.** Identical to the 6BQ6-GA except for heater ratings. Refer to the 6BQ6-GA Description and Rating sheet for complete data.

**25BQ6-GTB Beam Pentode.** Identical to the 6BQ6-GTB except for heater ratings listed below. Refer to the 6BQ6-GTB Description and Rating sheet for complete data.

Heater Voltage, AC or DC .....	25.0 Volts
Heater Current .....	0.3 Amperes

**25C5 Beam Pentode.** Identical to the 50C5 except for heater ratings and addition of a controlled heater-warm-up characteristic. Refer to the 50C5 Description and Rating sheet for complete data.

**25CA5 Beam Pentode.** Identical to the 6CA5 except for heater ratings. Refer to the 6CA5 Description and Rating sheet for complete data.

**25CD6-GB Beam Pentode.** Identical to the 6CD6-GA except for heater ratings and addition of a controlled heater-warm-up characteristic. Refer to the 6CD6-GA Description and Rating sheet for complete data.

**25CU6 Beam Pentode.** Identical to the 6CU6 except for heater ratings. Refer to the 6CU6 Description and Rating sheet for complete data.

