



6LF6

Color Television Type
**HORIZONTAL DEFLECTION
 AMPLIFIER**

Beam Pentode

Construction.....Compactron T-12
 BaseE12-74
 Top CapC1-1
 Basing12GW
 Outline
 Maximum Diameter1.563 In.
 Maximum Seated Height4.570 In.
 Maximum Overall Height4.950 In.



ELECTRICAL DATA

HEATER OPERATION

Heater Voltage 6.3 Volts
 Heater Current 2.0 Amp.

DIRECT INTERELECTRODE CAPACITANCES (Unshielded)

Grid to Plate 3.0 pf
 Input: g1 to (h + k + g2 + bp)..... 37 pf
 Output: p to (h + k + g2 + bp)..... 18.5 pf

RATINGS (Design Maximum Rating System)

Horizontal Deflection Amplifier

DC Plate Supply Voltage at Zero Current (Max.) 990 Volts
 Peak Positive Plate Voltage⁽¹⁾ (Max.) 8000 Volts
 Beam Plate Voltage (Max.) 50 Volts
 Grid No. 2 Voltage (Max.) 275 Volts
 Peak Negative Grid No. 1 Voltage (Max.) 550 Volts
 Plate Dissipation (Max.) 40 Watts
 Peak Cathode Current (Max.)..... 1400 Ma
 Beam Plate Circuit Resistance (Max.) 0.01 Megohms
 Bulb Temperature (At Hottest Point) (Max.) 300 °C

AVERAGE CHARACTERISTICS (Measured Under Pulse Conditions)

	Max.	Min.	During Flyback
Plate Voltage	160	50	7000 Volts
Grid No. 2 Voltage	160	175	175 Volts
Grid No. 1 Voltage	0	-10	-185 Volts
Beam Plate Voltage	Tied to Cathode		
Plate Current	1400	800	<0.05 Ma
Grid No. 2 Current	45	70	— Ma

NOTE:

(1) Maximum pulse duration is 22% of a cycle, maximum 18 μsec.