



6SQ7
6SQ7-GT/G

6SQ7, 6SQ7-GT/G

DUPLEX-DIODE HIGH-MU TRIODE

		Coated Unipotential Cathode	
Heater Voltage	6.3	a-c or d-c volts	
Heater Current	0.3	amp.	
Direct Interelectrode Cap.	6SQ7 Δ	6SQ7-GT/G \bullet	
Triode Unit:			
Grid to Plate	1.6	1.8	μf
Grid to Cathode	3.2	4.2	μf
Plate to Cathode	3.0	3.4	μf
Maximum Overall Length	2-5/8"	3-5/16"	
Maximum Seated Height	2-1/16"	2-3/4"	
Maximum Diameter	1-5/16"	1-5/16"	
Bulb	Metal Shell, MT-8	T-9	
Base	{ Small Wafer Octal 8-Pin 8Q	{ Small Wafer Octal 8-Pin, Sleeve GT-8Q	
Basing Designation			
Pin 1	{ 6SQ7, Shell 6SQ7-GT/G, Base Sleeve	Pin 4 - Diode Plate #2	
Pin 2	Triode Grid	Pin 5 - Diode Plate #1	
Pin 3	Cathode	Pin 6 - Triode Plate	
Pin 7	Heater	Pin 7 - Heater	
Pin 8	Heater	Pin 8 - Heater	
Mounting Position	Any		



BOTTOM VIEW

Maximum Ratings Are Design-Center Values

TRIODE UNIT

Plate Voltage	300 max. volts	
D-C Heater-Cathode Potential	100 max. volts	
Characteristics - Class A₂ Amplifier:		
Heater	6.3	6.3 volts
Plate	100	250 volts
Grid	-1	-2 volts
Amp. Fact.	100	100
Plate Res.	11000	91000 ohms
Transcond.	900	1100 μmhos
Plate Cur.	0.4	0.9 ma.

Typical Operation—Resistance-Coupled Amplifier:
Same as Type 75 in RESISTANCE-COUPLED AMPLIFIER CHART.

DIODE UNITS—Two

Consideration of these units is given under Type 85. Circuits will be similar to those shown for Type 55 with fixed bias. Diode biasing of the triode unit of the 6SQ7 or 6SQ7-GT/G is not suitable. Diode curves under Type 6B7 apply to the 6SQ7 and 6SQ7-GT/G.

- Δ with shell connected to cathode. Values are approximate.
- \bullet with no external shield. Values are approximate.

The curve under Type 75 also applies to the 6SQ7 and the 6SQ7-GT/G.

← indicates a change.


6SQ7



6SQ7

AVERAGE PLATE CHARACTERISTICS TRIODE UNIT

$E_f = 6.3$ VOLTS






6SQ7

6SQ7

AVERAGE PLATE CHARACTERISTICS TRIODE UNIT

$E_f = 6.3$ VOLTS



AUG. 13, 1941

RCA RADITRON DIVISION
RCA MANUFACTURING COMPANY, INC.

92C-6310