



### SPECIFICATIONS

- 1. RATING : 2.5W/6.3A 250VAC  
10A 250VAC
- 2. WITHSTAND VOLTAGE : AC 2000V 1 Min.
- 3. INSULATION RESISTANCE : MORE THAN 100MΩ  
(at DC 500V)
- 4. OPERATING TEMPERATURE : -25° C TO +85° C (MAX)

5. SAFETY   

8D	PIN	2	Bsp1-1/2H	t=2.0	NI-Plated	Q101-08D
8A	CONNECTOR	1	Bsp1-1/2H	t=0.8	NI-Plated	Q101-08A
8C	FUSE HOLDER(SHORT)	2	Bsp1-1/2H	t=0.5	NI-Plated	Q101-08C
8B	TERMINAL(SHORT)	3	Bsp1-1/2H	t=0.8	SN-Plated	Q101-08B
3B	CENTER TERMINAL	1	Bsp1-1/2H	t=2.0	NI-Plated	Q101-03B
2B	EDGE TERMINAL	2	Bsp1-1/2H	t=2.0	NI-Plated	Q101-02B
1J	FUSE COVER	1	NYLON#66	94V2 Or 94V0		Q101-01J
1H	BODY	1	NYLON#66	94V2 Or 94V0		Q101-01H1